IP65 AC220V SMD2835 Rigid LED Strip Lights Waterproof Bar Aluminum Magnesium Material

Basic Information

- Place of Origin:
- Guangdong, China(Mainland)
- Brand Name:Certification:
- SUNLED CE, EMC, LVD, R₀SH
- Model Number:
- Minimum Order Quantity:
- Packaging Details:
- Supply Ability:
- SL-XS-2835-60P /: 500
- : Carton:125*19*20cm 200pcs/carton
 - 50000pieces per day



Product Specification

- PCB Size:Material:
- LED Type:
- LED Quantity:
- CRI(Ra):
- Official.
- Luminous Flux/M:
- Power:
- IP Rating:
- Highlight:

5mm
Aluminum+Magnesium
SMD2835
60 Leds
80
200lm/m
4w/m
IP65
led rigid strip light bars, solid led light stri



More Images



220V High Quality IP65 AC220V SMD2835 Waterproof LED rigid light bar

Feature:

- 1. Driverless(no need connect power supply);
- 2. Waterproof , misty , transparent, milk cover optional;
- 3. The voltage is stable;

4. Low consumption, generate the same luminance only with 6% power consumption as a

traditional lamp;

5. Meanwhile lamp beads which also integrates a capacitive resistance, so that electronic components do not need to be on board the auxiliary light bar, thus increasing the stability of the product;

6. Long life span, no filament structure, no heating more than six years for normal use;

Application:

Home, Hotels, Meeting rooms, Offices, Commercial Purposes, Institution Buildings, Schools, Hospitals, Places where energy saving and high color rendering index lightings required.



Advantage:

- 1. LED Strip light source with long life span, 50000 hours;
- 2. LED Strip light source benefit to environment protection;
- 3. LED Strip light source is safe and with high reliability;
- 4. LED Strip light source with high luminous efficiency

Parameter: Item No.:	SL-XS-2835-60P	SL-XS-2835-120P	SL-XS-2835-180P
Strip Size(±0.2mm):	H6.5XW11mm	H6.5XW13.3mm	H7.5XW16mm
PCB Size:	W=5mm	W=6.4mm	W=10mm
Wire Type:	Aluminum+Magnesium Alloy wire 0.18*20pcs=0.5mm ²	Aluminum+Magnesium Alloy wire 0.18*20pcs=0.5mm ²	Aluminum+Magnesium Alloy wire 0.18*20pcs=0.5mm ²
LED Type:	SMD2835/0.2W/18- 20LM/pcs (Against sulfurization)	SMD2835/0.2W/18- 20LM/pcs (Against sulfurization)	SMD2835/0.2W/18-20LM/pcs (Against sulfurization)
LED Q'ty/M:	60LED/M	120LED/M	180LED/M
LED Chip:	3A Chip	3A Chip	3A Chip
CRI.:	Ra=70-80	Ra=70-80	Ra=70-80
Luminous Flux/M:	200LM/M (Actual measurement value)	500LM/M (Actual measurement value)	800LM/M (Actual measurement value)
Power(±0.5W):	4W/M	5W/M	10W/M

Power Factor:	PF=0.93	PF=0.93	PF=0.93
Input Volt.:		AC220V/240V/110V,50- 60Hz	AC220V/240V/110V,50-60Hz
Insulation Strength:	>4MΩ	>4MΩ	>4ΜΩ
Electrical Strength:	3750V	3750V	3750V
IP Rating:	IP65	IP65	IP65
Cutting Unit:	1 Meter	1 Meter	1 Meter
LED Color:	W(6000-7000K) WW(2800-3200K)	W(6000-7000K) WW(2800-3200K)	W(6000-7000K) WW(2800-3200K)
Packing Detail:	50M/Roll/Ctn 32X32X17cm/G.W: 7.0KG	50M/Roll/Ctn 32X32X17cm/G.W: 7.5KG	50M/Roll/Ctn 32X32X17cm/G.W: 13.0KG



